


# SKY 156



## Inverter 1Phase

**NEW**



Made in ITALY

### Technical Data SKY 156

Main Voltage	230/240 V
Phase	1
Frequency	50/60 Hz
Real Current (25%)	13,5
Real Power (25%)	3,1 KVA
Power Factor	0,65
Efficiency	80 %
No Load Voltage	74 V
Current Range	5-120 A
Welding Current 25% (25°C)	120 A
Welding Current 60% (25°C)	85 A
Welding Current 100% (25°C)	70 A

### Features SKY 156

Earth Clamp - Cable/E.Holder	10 mm <sup>2</sup>
Degree of Protection	IP 22
Insulation Class	H
Work Temperature	40°C
Safety Approved	
Length/Width/Height (mm)	330x135x240
Weight	4,2 Kg

The data is measured at an environment temperature of 25 °C

Materials	Welding Process	Environments	Main Features
<ul style="list-style-type: none"> <li>Mild Steels</li> <li>Stainless Steels</li> <li>Castings</li> </ul>	<ul style="list-style-type: none"> <li>Electrode Welding</li> <li>TIG Scratch Start Welding</li> </ul>	<ul style="list-style-type: none"> <li>Light Fabrications</li> <li>Special Maintenance</li> <li>Ordinary Maintenance</li> <li>Auto repair</li> <li>Building and plumbing</li> <li>Electricians and installers</li> <li>Workshops</li> </ul>	<ul style="list-style-type: none"> <li>Inverter Technology</li> <li>3,25Ø Electrode</li> <li>OK motogenerator</li> <li>Ease of operation</li> <li>Portable</li> <li>Fireproof plastic</li> </ul>